



### 900 Series

### Boiling pans 900

### GAS BOILING PAN, MG9-15 BM

#### DIMENSIONS

		Article	Packed
Length	mm	850,00	890,00
Depth	mm	900,00	1.040,00
Height	mm	850,00	1.240,00
Weigth	Kg	135,00	172,00
Volumen	m3	0,65	1,15

#### ELECTRICITY

Electric power	KW		0,05
230V -1+N		2x1,5+T - 2 A	
230V - III			
400V - III+N			

#### WATER

Not used

#### GAS

Power		KW	23,00
		Kcal/h	19.780,00
LPG		Consumption (kg/h)	1,82
		Pressure (g/cm2)	37,00
Natural Gas		Consumption (m3/h)	2,31
		Pressure (g/cm2)	18,00

#### STEAM

Not used

#### AIR

Not used

#### GAS BOILING PAN, MG9-15 BM

Made of stainless steel.

Bottom of the well in stainless steel AISI-316-L.

Capacity: 150 litres. Double jacket pan (bain-marie system).

Counterweighted folding lid.

Stainless steel burner, with safety valve and thermocouple.

Piezoelectric ignition.

Safety device for the bain-marie extinguishes the burner in the event of low water level.

Cold and hot water filling tap.

Drainage tap.

Filling tap and control tap for the level of the double jacket pan (bain-marie). Level indicator.

Over-pressure safety valve and manometer.

Power: 19800 kcal/h. (23 kW).

Electrical connection: 230 V -1+N+E.

Dimensions: 850 x 900 x 850 mm.

#### Certificate EQNET- CE

99AP54

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	645	860	500		Válvula electromagnética
DRAIN	300	860	110		
SOFT HOT WATER	120	860	110	1/2"	Prever llave de corte en la toma
COLD WATER	190	860	110	1/2"	Prever llave de corte en la toma
GAS	820	660	110	R.3/4"G	Prever regulador y llave de corte individual

